

SAFETY DATA SHEET

TestOxidase™ Reagent

SECTION 1: IDENTIFICATION

1.1. Product identifier

Trade name: TestOxidase™ Reagent
Product no.: PL.390, PL.390-125

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture: Laboratory use
 Restricted to professional and industrial use.
Uses advised against : None known.

1.3. Details of the supplier of the safety data sheet

Company and address: **Pro-Lab Diagnostics**
 20 Mural Street, Unit 4
 L4B 1K3 Richmond Hill, ON
 Canada
 Tel: +1-800-268-2341
 Fax: +1-905-731-0206
 www.pro-lab.com

E-mail: support@pro-lab.com
SDS date: 12/8/2025
SDS Version: 1.0

1.4. Emergency telephone number

Contact the poison control at 1-800-222-1222 (24/7) or use the webPOISONCONTROL® (triage.webpoisoncontrol.org) to get specific guidance for your case
 See also section 4 "First aid measures".

SECTION 2: HAZARD(S) IDENTIFICATION

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)

2.1. Classification of the substance or mixture

Flam. Liq. 2; H225, Highly flammable liquid and vapour.
 Eye Irrit. 2; H319, Causes serious eye irritation.
 STOT SE 3; H336, May cause drowsiness or dizziness.

2.2. Label elements

Hazard pictogram(s):



<i>Signal word:</i>	Danger
<i>Hazard statement(s):</i>	Highly flammable liquid and vapour. (H225) Causes serious eye irritation. (H319) May cause drowsiness or dizziness. (H336)
<i>Precautionary statement(s):</i>	
<i>General:</i>	Not applicable.
<i>Prevention:</i>	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210) Keep container tightly closed. (P233) Avoid breathing mist/vapour. (P261) Wear eye protection/protective gloves/protective clothing. (P280)
<i>Response:</i>	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. (P305+P351+P338) Call a POISON CENTER/doctor if you feel unwell. (P312) If eye irritation persists: Get medical advice/attention. (P337+P313) In case of fire: Use water mist/carbon dioxide/alcohol-resistant foam to extinguish. (P370+P378)
<i>Storage:</i>	Store in a well-ventilated place. Keep container tightly closed. (P403+P233) Store in a well-ventilated place. Keep cool. (P403+P235)
<i>Disposal:</i>	Dispose of contents/container in accordance with local regulation. (P501)

2.3. Other hazards

Additional warnings: The material contains peroxide forming substances, which can form hazardous levels of peroxides e.g. during distillation, evaporation or extraction.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Not applicable. This product is a mixture.

3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
propan-2-ol;isopropyl alcohol;isopropanol	CAS No.: 67-63-0	80-95%	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	

Where the concentration of an ingredient is expressed as a range the exact concentration has been withheld as a trade secret.

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

-

SECTION 4: FIRST-AID MEASURES

4.1. Description of first aid measures

<i>General information:</i>	If breathing is irregular, drowsiness, loss of consciousness or cramps: Call 911 and give immediate treatment (first aid). Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.
<i>Inhalation:</i>	Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.
<i>Skin contact:</i>	Upon irritation: rinse with water. In the event of continued irritation, seek medical assistance.
<i>Eye contact:</i>	If in eyes: Flush eyes immediately with plenty of water or isotonic water (20-30 °C) for at least 5 minutes and continue until irritation stops. Remove contact lenses. Make sure to flush under upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.
<i>Ingestion:</i>	If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.
<i>Burns:</i>	Rinse with water until pain stops then continue to rinse for 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

If eye irritation persists: Get medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: FIRE-FIGHTING MEASURES**5.1. Extinguishing media**

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.
Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Highly flammable liquid and vapour.

In use may form flammable/explosive vapour-air mixture.

Fire will result in dense smoke. Exposure to combustion products may harm your health.

Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO₂)

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact the Poison Help Line on 1-800-222-1222 (24/7) in order to obtain further advice.

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1. Personal precautions, protective equipment and emergency procedures**

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

Ensure adequate ventilation, especially in confined areas.

Avoid inhalation of vapours from spilled material.

Contaminated areas may be slippery.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

Keep unauthorized persons away from the spill

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Ground and bond container and receiving equipment.

Use explosion-proof electrical/lighting/ventilating equipment.

Use non-sparking tools.

Take action to prevent static discharges.

The product should be tested for peroxides before distillation or evaporation and tested for peroxide formation or discarded after 1 year.

Peroxide formation may be present anywhere in the container, including the sides, bottom, exterior and threaded cap. Peroxide formation in ppm concentrations may not be visually observable and must be identified through the use of appropriate testing procedures. If any of the following conditions exist, the material may be explosively unstable and will require stabilization prior to use:

1. Material appears to be degraded and or contaminated.
2. Material appears to be discolored.
3. Deterioration or distortion of storage container.
4. Thermal shock (sunlight).
5. Age of material exceeds recommended storage time.

Avoid contact during pregnancy and while nursing.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers and store protected from moisture and light. Containers should be dated when opened and tested periodically for the presence of peroxides. Do not exceed storage time limits.

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Take action to prevent static discharges.

Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

Recommended storage material: Keep only in original packaging.

Liquid class: Flammable liquid / Class IB (NFPA 30)

Storage conditions: Room temperature (15° to 30°C).

Incompatible materials: Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

propan-2-ol;isopropyl alcohol;isopropanol

Short term exposure limit (STEL) (ACGIH TLV) (ppm): 400

Short term exposure limit (STEL) (NIOSH REL) (ppm): 500

Long term exposure limit (OSHA Table Z-1) (mg/m³): 980

Long term exposure limit (OSHA Table Z-1) (ppm): 400

Long term exposure limit (ACGIH TLV) (ppm): 200

Part 1910 - Occupational Safety and Health Standards (29 CFR 1910.1000 TABLE Z-1 - Limits for Air Contaminants)

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.


<i>General recommendations:</i>	Smoking, drinking and consumption of food is not allowed in the work area.
<i>Exposure scenarios:</i>	There are no exposure scenarios implemented for this product.
<i>Exposure limits:</i>	Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.
<i>Appropriate technical measures:</i>	The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked. Apply standard precautions during use of the product. Avoid inhalation of vapours.
<i>Hygiene measures:</i>	In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Pay special attention to hands, forearms and face.
<i>Measures to avoid environmental exposure:</i>	No specific requirements.

Individual protection measures, such as personal protective equipment


Generally: Use only protective equipment with a recognized certification mark, e.g. the UL mark.

Respiratory Equipment:
No specific requirements.


Skin protection:

Recommended	Type/Category	Standards	
Dedicated work clothing should be worn.	-	-	

Hand protection:

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Nitrile	-	-	EN374-2	

Eye protection:

Type	Standards	
Safety glasses	EN166	

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

<i>Physical state:</i>	Liquid
<i>Color:</i>	No data available.
<i>Odor:</i>	No data available.
<i>Odor threshold (ppm):</i>	No data available.
<i>pH:</i>	4.5
<i>Density (g/cm³):</i>	No data available.
<i>Kinematic viscosity:</i>	No data available.
<i>Particle characteristics:</i>	Does not apply to liquids.

Phase changes

<i>Melting point/freezing point (°F):</i>	No data available.
<i>Softening point/range (°F):</i>	Does not apply to liquids.
<i>Boiling point (°F):</i>	180.5
<i>Boiling point (°C):</i>	82.5
<i>Vapor pressure:</i>	No data available.
<i>Relative vapor density:</i>	No data available.
<i>Decomposition temperature (°F):</i>	No data available.

Data on fire and explosion hazards

<i>Flash point (°F):</i>	64.9
<i>Flash point (°C):</i>	18.3
<i>Flammability (°F):</i>	The material is ignitable.
<i>Auto-ignition temperature (°F):</i>	No data available.
<i>Explosion limits (% v/v):</i>	No data available.

Solubility

<i>Solubility in water:</i>	No data available.
<i>n-octanol/water coefficient (LogKow):</i>	No data available.
<i>Solubility in fat (g/L):</i>	No data available.

9.2. Other information

<i>Other physical and chemical parameters:</i>	No data available.
--	--------------------

Oxidizing properties: No data available.

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions, including those associated with foreseeable emergencies

None known.

10.4. Conditions to avoid

Avoid static electricity.

Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

Risk of formation of explosive peroxides when distilled, evaporated or otherwise concentrated.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Acute toxicity

Based on available data for the mixture, the classification criteria are not met.

Skin corrosion/irritation

Based on available data for the mixture, the classification criteria are not met.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory sensitisation

Based on available data for the mixture, the classification criteria are not met.

Skin sensitisation

Based on available data for the mixture, the classification criteria are not met.

Germ cell mutagenicity

Based on available data for the mixture, the classification criteria are not met.

Carcinogenicity

Based on available data for the mixture, the classification criteria are not met.

Reproductive toxicity

Based on available data for the mixture, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Based on available data for the mixture, the classification criteria are not met.

Aspiration hazard

Based on available data for the mixture, the classification criteria are not met.

Long term effects

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

Other information

propan-2-ol;isopropyl alcohol;isopropanol has been classified by IARC as a group 3 carcinogen.

SECTION 12: ECOLOGICAL INFORMATION**12.1. Toxicity**

Based on available data for the mixture, the classification criteria are not met.

12.2. Persistence and degradability

Based on available data for the mixture, the classification criteria are not met.

12.3. Bioaccumulative potential

Based on available data for the mixture, the classification criteria are not met.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. Other adverse effects

None known.




SECTION 13: DISPOSAL CONSIDERATIONS**RCRA Hazardous waste ("P" and "U" list) (40 CFR 261)**

None of the components are listed

Specific labelling**Contaminated packing**

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: TRANSPORT INFORMATION

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other informat ion:
DOT	UN1219	ISOPROPANOL (ISOPROPYL ALCOHOL)	Transport hazard class: 3 Label: 3 Classification code: F1 	II	No	Limited quantities: 1 L Tunnel restriction code: (D/E) See below for additional information.
IMDG	UN1219	ISOPROPANOL (ISOPROPYL ALCOHOL)	Transport hazard class: 3 Label: 3 Classification code: F1 	II	No	Limited quantities: 1 L EmS: F-E S-D See below for additional information.
IATA	UN1219	ISOPROPANOL (ISOPROPYL ALCOHOL)	Transport hazard class: 3 Label: 3 Classification code: F1 	II	No	See below for additional information.

* Packing group

** Environmental hazards

Additional information

This product is within scope of the regulations of transport of dangerous goods.

DOT / See § 172.101 Hazardous Materials Table for any information on special provisions, requirements, or warnings in connection with transport. See § 172.602, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to IMO instruments

No data available.

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. U.S. Federal regulations

<i>TSCA (the non-confidential portion):</i>	propan-2-ol;isopropyl alcohol;isopropanol is listed
<i>Clean Air Act:</i>	None of the components are listed
<i>EPCRA Section 302:</i>	None of the components are listed
<i>EPCRA Section 304:</i>	None of the components are listed
<i>EPCRA section 313:</i>	propan-2-ol;isopropyl alcohol;isopropanol is listed
<i>CERCLA:</i>	None of the components are listed
<i>Hazardous chemical inventory reporting:</i>	This product is subject to Tier II reporting.

State regulations

<i>California / Prop. 65:</i>	None of the components are listed
<i>Massachusetts / Right To Know Act:</i>	propan-2-ol;isopropyl alcohol;isopropanol is listed
<i>New Jersey / Right To Know Act:</i>	propan-2-ol;isopropyl alcohol;isopropanol / Substance number: 1076 propan-2-ol;isopropyl alcohol;isopropanol is on the Special Health Hazard Substance List
<i>New York / Right To Know Act:</i>	— propan-2-ol;isopropyl alcohol;isopropanol is listed propan-2-ol;isopropyl alcohol;isopropanol is regulated with a Treshold Reporting Quantity (TRQ) of: 0 pounds
<i>Pennsylvania / Right To Know Act:</i>	— propan-2-ol;isopropyl alcohol;isopropanol is listed propan-2-ol;isopropyl alcohol;isopropanol is hazardous to the environment (E)

15.4. Restrictions for application

Restricted to professional and industrial use.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

15.5. Demands for specific education

No specific requirements.

15.6. Additional information

Not applicable.

15.7. Chemical safety assessment

No

15.8. Sources

OSHA Hazard Communication Standard (29 CFR 1910.1200)

SECTION 16: OTHER INFORMATION

Full text of H-phrases as mentioned in section 3

H225, Highly flammable liquid and vapour.

H319, Causes serious eye irritation.

H336, May cause drowsiness or dizziness.

The full text of identified uses as mentioned in section 1

None known.

Abbreviations and acronyms

ACGIH = American Conference of Governmental Industrial Hygienists

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CERCLA = Comprehensive Environmental Response Compensation and Liability Act

DOT = Department of Transportation

EINECS = European Inventory of Existing Commercial chemical Substances

EPCRA = Emergency Planning and Community Right-To-Know Act

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

HCIS = Hazardous Chemical Information System

HNOC = Hazards Not Otherwise Classified

IARC = International Agency for Research on Cancer

IATA = International Air Transport Association

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

NFPA = National Fire Protection Association

NIOSH = National Institute for Occupational Safety and Health

OECD = Organisation for Economic Co-operation and Development

OSHA = Occupational Safety and Health Administration

PBT = Persistent, Bioaccumulative and Toxic

RCRA = Resource Conservation and Recovery Act

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SARA = Superfund Amendments and Reauthorization Act

SCL = A specific concentration limit.

STEL = Short-term exposure limits

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TSCA = The Toxic Substances Control Act

TWA = Time weighted average

UN = United Nations

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the mixture in regard of health hazards is in accordance with the calculation methods given by HCS (29 CFR 1910.1200).

The classification of the mixture in regard to physical hazards has been based on experimental data.

The safety data sheet is validated by

Pro-Lab Diagnostics

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product.

Information in this safety data sheet cannot be used as a product specification.

Country-language: US-en